

# 16 SEER Heat Pump Models

## 16 SEER - 9K to 36K BTU

### Single-Zone Heat Pump

### Mini-Splits 9K to 12K BTU - 16 SEER



**R-410A**

Model	Indoor Unit		GHH09(2.6)LSA4DL	GHH12(3.5)LSA4DL	GHH09(2.6)LSK4DL	GHH12(3.5)LSK4DL
	Outdoor Unit		GXH09(2.6)LSA4DL	GXH12(3.5)LSA4DL	GXH09(2.6)LSK4DL	GXH12(3.5)LSK4DL
Function		Cooling/Heating				
Capacity	Cooling	Btu/h	9000	12000	9000	12000
	Heating	Btu/h	9600	13000	9500	13000
SEER/HSPF		Btu/W (HSPF)	16 (9)			
Power Supply		Ph-V-Hz	1-115-60		1-208/230-60	
Maximum Over Current Protection		A	25	30	15	
Minimum Current (MCA)		A	17	20	9	
Airflow Volume	Indoor	CFM	317	400	317	400
<b>Indoor Unit</b>						
Sound Pressure Level	Indoor	dB(A)(SH/H/M/L)	42/38/32/28	43/39/35/29	43/38/34/28	45/39/35/29
Outline Dimension	WxHxD	mm	790 x 275 x 200	845 x 289 x 209	790 x 275 x 200	845 x 289 x 209
		inch	31.1 x 10.8 x 7.8	33.3 x 11.4 x 8.3	31.1 x 10.8 x 7.9	33.3 x 11.4 x 8.2
Package Dimension	WxHxD	mm	866 x 367 x 271	921 x 379 x 281	866 x 367 x 271	921 x 379 x 281
		inch	34.1 x 14.4 x 10.7	36.3 x 14.9 x 11.1	34.1 x 14.4 x 10.7	36.1 x 15 x 11
Net Weight/Gross Weight	Indoor	kg	9/11	10.5/12.5	9/11	10.5/12.5
		lb	19.8/24.3	29/31.5	19.8/24.3	23.2/27.6
<b>Outdoor Unit</b>						
Sound Pressure Level	Outdoor	dB(A)	51		52	53
Piping Connection	Suction	inch (mm)	3/8 (9.52)			
	Liquid	inch (mm)	1/4 (6)			
Outline Dimension	WxHxD	mm	848 x 540 x 320		776 x 540 x 320	
		inch	33.4 x 21.3 x 12.6		30.6 x 21.2 x 12.6	
Package Dimension	WxHxD	mm	881 x 363 x 595	881 x 595 x 363	823 x 595 x 358	
		inch	34.7 x 14.3 x 23.4	34.7 x 23.4 x 14.3	34.7 x 14.3 x 23.4	34.7 x 23.4 x 14.3
Net Weight/Gross Weight	Outdoor	kg	27/29.5	29/31.5	30/32.5	32/34.5
		lb	59.5/65	63.9/69.5	66.2/71.7	70.6/76.1
<b>Accessories</b>						
Remote Control - WLRC4F			1013845			
Line Set SKU Number with Wire			05-0200			

Note: Line Sets 25 feet or less require no additional refrigerant.



# 16 SEER Heat Pump Models

## 16 SEER - 9K to 36K BTU (continued)

### Single-Zone Heat Pump

### Mini-Splits 18K to 36K BTU - 16 SEER



**R-410A**

Model		Indoor Unit	GHH18(5.3)LSK4DL	GHH24(7.0)LSK4DL	GHH30(8.8)LSK4DL	GHH36(10.6)LSK4DL
		Outdoor Unit	GXH18(5.3)LSK4DL	GXH24(7.0)LSK4DL	GXH30(8.8)LSK4DL	GXH36(10.6)LSK4DL
Function		Cooling/Heating				
Capacity	Cooling	Btu/h	18000	22000	28000	33600
	Heating	Btu/h	19000	23000	28400	34600
SEER/HSPF		Btu/W (HSPF)	16 (9)		16 (8.2)	
Power Supply		Ph-V-Hz	1-208/230-60			
Maximum Over Current Protection		A	25		30	40
Minimum Current (MCA)		A	16		20	24
Airflow Volume	Indoor	CFM	470	760	706/618/0/530/0/412/0	736/647/0/530/0/412/0
<b>Indoor Unit</b>						
Sound Pressure Level	Indoor	dB(A)(SH/H/M/L)	46/42/39/36	48/44/40/36	56/53/46/41	
Outline Dimension	WxHxD	mm	970 x 300 x 224	1078 x 325 x 242	1350 x 326 x 253	
		inch	38.2 x 11.8 x 8.8	42.4 x 12.8 x 9.6	53.15 x 12.835 x 9.961	
Package Dimension	WxHxD	mm	1041 x 383 x 320	1148 x 413 x 350	1441 x 421 x 358	
		inch	41 x 15 x 12.6	45 x 16.1 x 13.2	56.732 x 16.575 x 14.094	
Net Weight/Gross Weight	Indoor	kg	12.5/15.5	17/20.5	19/26	
		lb	27.6/34.2	37.5/45.2	41.9/57.3	
<b>Outdoor Unit</b>						
Sound Pressure Level	Outdoor	dB(A)	56	59	62	65
Piping Connection	Suction	inch (mm)	1/2 (12)	5/8 (16)		
	Liquid	inch (mm)	1/4 (6)			
Outline Dimension	WxHxD	mm	955 x 700 x 396		980 x 790 x 427	
		inch	37.6 x 27.5 x 15.6		38.583 x 31.102 x 16.811	
Package Dimension	WxHxD	mm	1029 x 750 x 458		1083 x 488 x 855	
		inch	40.5 x 18 x 29.5		42.638 x 19.213 x 33.661	
Net Weight/Gross Weight	Outdoor	kg	43.5/48	50/54.5	70/74	73/77
		lb	95.9/105.8	110.2/120.1	154.4/163.2	161.0/169.8
<b>Partners Choice</b>						
Remote Control			WLRC4F (Partners Choice SKU 1013845)		RC (Partners Choice SKU 1007701)	
Line Set SKU Number with Wire			05-0202	1016619		

Note: Line Sets 25 feet or less require no additional refrigerant.