

Up to 23 SEER Heat Pump Models



WLRC4F Remote

SKU Number **1013845**

Up to 23 SEER - 9K to 36K BTU

Single-Zone Heat Pump

Mini-Splits 9K to 12K BTU - Up to 23 SEER



| Model | Indoor Unit | | GHH09(2.6)LUK4DH | GHH12(3.5)LUK4DH |
|---------------------------------|--------------|-----------------|-----------------------|-----------------------|
| | Outdoor Unit | | GXH09(2.6)LSK4DH | GXH12(3.5)LSK4DH |
| Function | | | Cooling/Heating | |
| Capacity | Cooling | Btu/h | 9000 | 12000 |
| | Heating | Btu/h | 11000 | 13000 |
| SEER/HSPF | | Btu/W (HSPF) | 23 (10.5) | 22 (10.1) |
| Power Supply | | Ph-V-Hz | 1-208/230-60 | |
| Maximum Over Current Protection | | A | 15 | |
| Minimum Current (MCA) | | A | 9 | |
| Airflow Volume | Indoor | CFM | 376/288/241/171 | 400/288/241/171 |
| Indoor Unit | | | | |
| Sound Pressure Level | Indoor | dB(A)(SH/H/M/L) | 43/39/35/29 | 45/39/35/29 |
| Outline Dimension | WxHxD | mm | 845 x 289 x 209 | |
| | | inch | 33.26 x 11.37 x 8.28 | 33.26 x 11.37 x 8.23 |
| Package Dimension | WxHxD | mm | 921 x 379 x 281 | |
| | | inch | 36.26 x 11.06 x 14.92 | 36.26 x 11.06 x 14.9 |
| Net Weight/Gross Weight | Indoor | kg | 10/12 | |
| | | lb | 22/26.5 | |
| Outdoor Unit | | | | |
| Sound Pressure Level | Outdoor | dB(A) | 53 | 54 |
| Piping Connection | Suction | inch (mm) | 3/8 (9.52) | 1/2 (12) |
| | Liquid | inch (mm) | 1/4 (6) | |
| Outline Dimension | WxHxD | mm | 848 x 540 x 320 | 848 x 592 x 320 |
| | | inch | 33.38 x 23.30 x 12.59 | 33.39 x 23.31 x 12.59 |
| Package Dimension | WxHxD | mm | 881 x 595 x 363 | 881 x 645 x 363 |
| | | inch | 34.68 x 14.9 x 23.43 | 34.68 x 14.29 x 25.39 |
| Net Weight/Gross Weight | Outdoor | kg | 35.5/38 | 39/42 |
| | | lb | 78.3/83.8 | 86/92.6 |
| Partners Choice | | | | |
| Line Set SKU Number with Wire | | | 05-0200 | 05-0202 |

Note: Line Sets 25 feet or less require no additional refrigerant.

Up to 23 SEER Heat Pump Models

Up to 23 SEER - 9K to 36K BTU (continued)

Single-Zone Heat Pump

Mini-Splits 12K to 36K BTU - Up to 23 SEER



R-410A

| Model | Indoor Unit | | GHH18(5.3)LUK4DH | GHH24(7.0)LUK4DH | GHH36(10.6)LUK4DH |
|---------------------------------|--------------|-----------------|-----------------------|-----------------------|--------------------|
| | Outdoor Unit | | GXH18(5.3)LSK4DH | GXH24(7.0)LSK4DH | GXH36(10.6)LSK4DH |
| Function | | | Cooling/Heating | | |
| Capacity | Cooling | Btu/h | 18000 | 22000 | 33600 |
| | Heating | Btu/h | 19800 | 23000 | 34600 |
| SEER/HSPF | | Btu/W (HSPF) | 20 (10) | | 18 (9) |
| Power Supply | | Ph-V-Hz | 1-208/230-60 | | |
| Maximum Over Current Protection | | A | 25 | 30 | 30 |
| Minimum Current (MCA) | | A | 16 | 20 | 24 |
| Airflow Volume | Indoor | CFM | 530/488/412/335 | 706/647/588/530 | 736 |
| Indoor Unit | | | | | |
| Sound Pressure Level | Indoor | dB(A)(SH/H/M/L) | 47/43/40/39 | 48/44/40/36 | 52/48/43/35 |
| Outline Dimension | WxHxD | mm | 970 x 300 x 224 | 1078 x 325 x 242 | 1350x326x253 |
| | | inch | 38.19 x 11.81 x 8.82 | 42.44 x 12.79 x 9.68 | 53.2x12.8x10.0 |
| Package Dimension | WxHxD | mm | 1041 x 383 x 320 | 1148 x 413 x 350 | 1441x421x358 |
| | | inch | 40.98 x 15.08 x 12.59 | 45.19 x 16.26 x 13.78 | 56.7x16.6x14.1 |
| Net Weight/Gross Weight | Indoor | kg | 12.5/15.5 | 15.5/19 | 19/23.5 |
| | | lb | 27.6/34.2 | 34.2/41.9 | 41.9/51.8 |
| Outdoor Unit | | | | | |
| Sound Pressure Level | Outdoor | dB(A) | 55 | 59 | 62 |
| Piping Connection | Suction | inch (mm) | 5/8 (16) | | |
| | Liquid | inch (mm) | 1/4 (6) | | |
| Outline Dimension | WxHxD | mm | 955 x 700 x 396 | 980 x 790 x 427 | |
| | | inch | 37.59 x 27.56 x 15.59 | 38.58 x 31.10 x 16.81 | 38.6 x 31.1 x 16.8 |
| Package Dimension | WxHxD | mm | 1029 x 750 x 458 | 1083 x 488 x 855 | 1083 x 855 x 488 |
| | | inch | 40.51 x 29.53 x 18.03 | 42.63 x 19.21 x 33.66 | 42.6 x 19.2 x 33.6 |
| Net Weight/Gross Weight | Outdoor | kg | 48/52.5 | 64.5/69.5 | 73/77 |
| | | lb | 105.8/115.8 | 142.2/153.2 | 161/169.8 |
| Partners Choice | | | | | |
| Line Set SKU Number with Wire | | | 1016619 | | |

Note: Line Sets 25 feet or less require no additional refrigerant.

